

RECEIVED
CENTRAL FAX CENTER

NOV 06 2006

Felix Buechi *et al.*
Appl. No.: 10/608,088**AMENDMENTS TO THE CLAIMS**

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

The following listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method of providing humidity to an electrolyte membrane of a fuel cell, said membrane running between a cell anode area and a cell cathode area, comprising the steps of:

extracting humidity from fluid flowing from one of said anode and cathode areas, and

charging fluid flowing into said one of said anode and cathode areas with said humidity, ~~wherein flow channels are separated from each other in a fluid tight manner~~

routing said fluid flowing from said one of said anode and cathode areas along an opposite side of a membrane to said fluid flowing into said one of said anode and cathode areas, said membrane being pervious to said humidity such that said exchanged fluid passes through said membrane, and

discharging said fluid flowing from one of said anode and cathode areas.

2. (cancelled)

3. (currently amended) The method according to claim 2~~1~~, wherein said fluid flowing from one of said anode and cathode areas and said fluid flowing into said one of said anode and cathode areas comprise one of a same, opposite, and cross-current-routed direction of flow.

Felix Buechi *et al.*
Appl. No.: 10/608,088

4. (original) The method according to claim 1, wherein said fuel cell comprises a plurality of fuel cells each comprising separate channels for accommodating flowing fluid, said plurality of fuel cells combine to form a fuel stack, and each of said plurality of fuel cells comprise a dehumidification unit.

5. (original) The method according to claim 4, wherein a separate membrane section pervious to humidity is assigned to each cathode area of each of said plurality of fuel cells.

6. (currently amended) The method according to claim 21, wherein said fuel cell comprises a plurality of fuel cells each comprising separate channels for accommodating flowing fluid, said plurality of fuel cells combine to form a fuel stack, and each of said plurality of fuel cells comprise a dehumidification unit.

7. (original) The method according to claim 6, wherein a separate membrane section pervious to humidity is assigned to each cathode area of each of said plurality of fuel cells.

8. (original) The method according to claim 3, wherein said fuel cell comprises a plurality of fuel cells each comprising separate channels for accommodating flowing fluid, said plurality of fuel cells combine to form a fuel stack, and each of said plurality of fuel cells comprise a dehumidification unit.

9. (original) The method according to claim 8, wherein a separate membrane section pervious to humidity is assigned to each cathode area of each of said plurality of fuel cells.

10. (currently amended) A fuel cell, comprising:

- a cathode area,
- an anode area,

Felix Buechi *et al.*
Appl. No.: 10/608,088

- an electrolyte membrane;
- an inflow line for accommodating fluid to one of said cathode area and anode area,
- an outflow line for accommodating fluid from said one of said cathode area and anode area, and
- a humidity exchanger functionally associated with one of said cathode area and anode area and positioned along one of said inflow line and out flow line, said exchanger providing humidification of fluid supplied to said one of said cathode area and anode area by extracting humidity from fluid flowing from one of said anode and cathode areas, and charging fluid flowing into said one of said anode and cathode areas with said humidity, ~~wherein flow channels are separated from each other in a fluid tight manner~~ wherein said humidity exchanger comprises a humidifying and dehumidifying zone separated by a humidity pervious membrane, and wherein said inflow line is positioned in said humidifying zone and the outflow line is positioned in said dehumidifying zone.

11. (cancelled)

12. (currently amended) The fuel cell according to claim ~~11~~10, further ~~comprising an electrolyte membrane, wherein same materials are used for said electrolyte membrane and said humidity pervious membranes.~~

13. (original) The fuel cell according to claim 12, wherein said electrolyte membrane and said humidity pervious membrane combine to form different portions of a single membrane.

14. (original) The fuel cell according to claim 10, further comprising a plurality of fuel cells combined to form a stack, wherein each of said plurality of fuel cells has a separate humidity exchanger connected to said cathode area of each of said plurality of fuel cells.

Felix Buechi *et al.*
Appl. No.: 10/608,088

15. (original) The fuel cell according to claim 14, wherein at least sections of one of said inflow and outflow lines of each of said plurality of fuel cells run through an adjacent one of said plurality of fuel cells.

16. (original) The fuel cell according to claim 10, further comprising a plurality of fuel cells combined to form a stack, wherein each of said plurality of fuel cells has a separate humidity exchanger connected exclusively to a cathode area of each of said plurality of fuel cells.

17. (original) The fuel cell according to claim 16, wherein at least sections of one of said inflow and outflow lines of each of said plurality of fuel cells run through an adjacent one of said plurality of fuel cells.

18. (currently amended) The fuel cell according to claim ~~11~~10, further comprising a plurality of fuel cells combined to form a stack, wherein each of said plurality of fuel cells has a separate humidity exchanger connected exclusively to a cathode area of each of said plurality of fuel cells.

19. (original) The fuel cell according to claim 18, wherein at least sections of one of said inflow and outflow lines of each of said plurality of fuel cells run through an adjacent one of said plurality of fuel cells.

20. (original) The fuel cell according to claim 12, further comprising a plurality of fuel cells combined to form a stack, wherein each of said plurality of fuel cells has a separate humidity exchanger connected exclusively to a cathode area of each of said plurality of fuel cells.

21. (original) The fuel cell according to claim 20, wherein at least sections of one of said inflow and outflow lines of each of said plurality of fuel cells run through an adjacent one of said plurality of fuel cells.

Felix Buechi *et al.*
Appl. No.: 10/608,088

22. (original) The fuel cell according to claim 13, further comprising a plurality of fuel cells combined to form a stack, wherein each of said plurality of fuel cells has a separate humidity exchanger connected exclusively to a cathode area of each of said plurality of fuel cells.

23. (original) The fuel cell according to claim 22, wherein at least sections of one of said inflow and outflow lines of each of said plurality of fuel cells run through an adjacent one of said plurality of fuel cells.